

## Portable Generators TPG

TSURUMI TPG-series portable generators are designed to withstand the severe conditions of construction jobsites or industrial applications, especially where extra durability and dependable, stable power are required. Ideal to supply the power to Tsurumi's single-phase submersible pumps and all your electrical power tools such as drills, saws, lighting and heaters due to AVR system.



TSURUMI PUMP x POWERED BY HONDA



Electric Starter available for TPG- 6000/7000HEL only



Wheel kit available as option

### Product Features and Advantages

- Powered by Made in Japan Honda OHV engine for efficient fuel and oil consumption with oil alert system to shut off motor if oil falls below safe operation level.
- Large Air Filter for superior emission control.
- Large, Silent Muffler to greatly reduce noise.
- Rubber Vibration Pads isolate generator/engine set for maximum protection and noise reduction.
- High Capacity Fuel Tank with Fuel Gauge for extended run-time.
- Volt Meter, Pilot Lamp and DC 12V Outlet are equipped as standard.
- Electric Starter makes free from extra work for start-up.

### Standard Accessories

• AC 16A European Type Plug	2pcs.
• DC 12V Plug w/Cord & Clip	1pc.
• Hexagon Wrench	1pc.

### Standard Specifications 50Hz

Model	TPG-3000HM	TPG-4000HM	TPG-6000HM	TPG-6000HEL	TPG-7000HM	TPG-7000HEL	
Engine Brand	HONDA						
Engine Model	GX160	GX240	GX340		GX390		
Displacement (cm <sup>3</sup> )	163	242	337		389		
Max. Output (kW / 4000rpm)	4.0	5.9	8.1		9.6		
Type	Air Cooled, 4-cycle, OHV Gasoline Engine						
Oil Alert System	Standard						
Ignition System	Transfer (C.D.I.)						
Electric Start	N/A		Standard		N/A	Standard	
Alternator	Self-exciting, 2-pole, Field Rotating Type, Single-phase						
Voltage Regulator	AVR						
Phase	Single						
AC Max. Output (kVA)	2.2	3.6	4.8		5.5		
AC Rated Output (kVA)	2.0	3.0	4.0		5.0		
Rated Voltage	220V / 50Hz						
AC Outlet	16A European Type (Receptacle)×2						
DC Outlet	12V-8.3A (Receptacle)×1						
Pilot Lamp	Standard						
Volt Meter	Standard						
Fuel Tank Capacity (ℓ)	16.0	25.0					
Continuous Operating Hours (hr: 100% Load)	14.1	15.1	10.1		9.0		
Sound Level (dB A / 7m)	71	73	75	75	76	76	
Dimensions (mm / L×W×H)	595×414×495		685×534×509				
Dry Weight (kgs)	45.8	69.5	78.2	81.2	82.0	85.0	

We reserve the right to change the specifications and designs for improvement without prior notice.